

IN THE CLAIMS:

Please amend Claims 1 and 2, cancel Claims 3-5, and add new Claims 6 and 7 as indicated below.

1. (Currently Amended) A data transfer method in an image formation system which is equipped with an image generation controller unit for generating bitmap image data of an image, an image formation unit for forming an image on a recording medium, an image processing controller unit for controlling the image formation unit and ~~also~~ for transferring image data at a timing requested by the image formation unit, and respective data signal lines for yellow, magenta, cyan and black to be used to transfer the image data between the image generation controller unit and the image processing controller unit, wherein

in a case where the number of image bearing bodies of the image formation unit is one, when a color image signal is transferred from the image generation controller unit to the image processing controller unit, the image signals of one color component for the four lines are simultaneously transferred by using the yellow, magenta, cyan and black signal lines repeatedly until the transfer of the image signals for one page ends, and then the image signals of the next color component are transferred, and

when a black-and-white image signal is transferred from the image generation controller unit to the image processing controller unit, the image signals of black color component ~~for the four lines~~ are simultaneously transferred by using the yellow, magenta, cyan and black signal lines, wherein the black-and-white image signal is

a binary signal and has a higher resolution than the color image signal repeatedly until the transfer of the image signals for one page ends.

2. (Currently Amended) A data transfer method in an image formation system which is equipped with an image generation controller unit for generating bitmap image data of an image, an image formation unit for forming an image on a recording medium, an image processing controller unit for controlling the image formation unit and for transferring image data at a timing requested by the image formation unit, and respective data signal lines for yellow, magenta, cyan and black to be used to transfer the image data between the image generation controller unit and the image processing controller unit according to Claim 1, wherein in a case where the number of the image bearing bodies of the image formation unit is four,

when ~~[[the]]~~ a color image signal is transferred from the image generation controller unit to the image processing controller unit, the image signals of the respective color components for the corresponding one line are simultaneously transferred respectively by using the yellow, magenta, cyan and black signal lines ~~repeatedly until the transfer of the image signals for one page ends,~~ and

when ~~[[the]]~~ a black-and-white image signal is transferred from the image generation controller unit to the image processing controller unit, the image signals of black color component ~~for the four lines~~ are simultaneously transferred by using the yellow, magenta, cyan and black signal lines, wherein the black-and-white image signal is a binary signal and has a higher resolution than the color image signal repeatedly until the

~~transfer of the image signals for one page ends.~~

3.-5. (Cancelled)

6. (New) An image formation system comprising:

an image generation controller unit for generating bitmap image data of an image;

an image formation unit for forming an image on a recording medium;

an image processing controller unit for controlling the image formation unit and for transferring image data at a timing requested by the image formation unit; and

respective data signal lines for yellow, magenta, cyan and black to be used to transfer the image data between the image generation controller unit and the image processing controller unit,

wherein in a case where the number of image bearing bodies of the image formation unit is one, when a color image signal is transferred from the image generation controller unit to the image processing controller unit, the image signals of one color component for the four lines are simultaneously transferred by using the yellow, magenta, cyan and black signal lines repeatedly until the transfer of the image signals for one page ends, and then the image signals of the next color component are transferred, and

when a black-and-white image signal is transferred from the image

generation controller unit to the image processing controller unit, the image signals of black color component are simultaneously transferred by using the yellow, magenta, cyan and black signal lines, wherein the black-and-white image signal is a binary signal and has a higher resolution than the color image signal.

7. (New) An image formation system comprising:

an image generation controller unit for generating bitmap image data of an image;

an image formation unit for forming an image on a recording medium;

an image processing controller unit for controlling the image formation unit and for transferring image data at a timing requested by the image formation unit; and

respective data signal lines for yellow, magenta, cyan and black to be used to transfer the image data between the image generation controller unit and the image processing controller unit,

wherein in a case where the number of the image bearing bodies of the image formation unit is four, when a color image signal is transferred from the image generation controller unit to the image processing controller unit, the image signals of the respective color components for the corresponding one line are simultaneously transferred respectively by using the yellow, magenta, cyan and black signal lines, and

when a black-and-white image signal is transferred from the image

generation controller unit to the image processing controller unit, the image signals of black color component are simultaneously transferred by using the yellow, magenta, cyan and black signals lines, wherein the black-and-white image signal is a binary signal and has a higher resolution than the color image signal.